

■ Comfort/Lifestyle

Cordless Radio with Lantern

MR009G



DMR056 / DMR055



Job Site Radio



MR001G / MR002G



MR006G / MR007G





LED Flashlight -ML001G



Cordless LED Worklight Cordless Flashlight ML002G





ML007G



Cordless Fan





Cordless Kettle

KT001G



DKT360



Cordless Coffee Maker DCM501



Accessories

AC adapter





Charging Time

40 Vision	DC40RA	DC40RC	ABV LITHIUMHON	DC18RC DC18RD	DC18SD
BL4020 2.0Ah	22 min	30 min	BL1815N 1.5Ah	15 min	30 min
BL4025 2.5Ah	28 min	38 min	BL1820B 2.0Ah	24 _{min}	45 min
BL4040 4.0Ah	45 min	67 min	BL1830B 3.0Ah	22 min	60 min
BL4050F 5.0Ah	50 min	85 min	BL1840B 4.0Ah	36 min	90 min
BL4080F 8.0Ah	76 min	170 min	BL1850B 5.0Ah	45 min	110 min
	•	•	BL1860B 6.0Ah	55 min	130 min

Cordless Cooler & Warmer Box

CW002G / CW001G / CW003G						
	CW002G	CW001G	CW003G			
Capacity	50 L (13.2 gal)	20 L (5.3 gal)	7 L (1.8 gal)			
Cooling system	Compressor	Compressor	Compressor			
Cooling Capacity	-18/-15/-10/-5/0/5/10°C	-18/-15/-10/-5/0/5/10°C	-18/-15/-10/-5/0/5/10°C			
	(0/5/15/25/30/40/50°F)	(0/5/15/25/30/40/50°F)	(0/5/15/25/30/40/50°F)			
Warming system	Heater	Heater	Heater			
Warming Capacity	30/35/40/45/50/55/60°C	30/35/40/45/50/55/60°C	30/35/40/45/50/55/60°C			
	(85/95/105/115/120/130/140°F)	(85/95/105/115/120/130/140°F)	(85/95/105/115/120/130/140°F)			
Run Time (hrs)	w/BLBL4040 X2, -18 / 5 / 60°C: 8 / 19.5 / 4.5	w/BLBL4040 X2, -18 / 5 / 60°C: 8 / 22.5 / 7	w/BLBL4040, -18/5/60°C: 5.5/13.5/5.5			
Cord Length	AC Adapter / Cigar Socket Cable: 2 / 2.5 m (6.5 / 8.2 ft)	AC Adapter / Cigar Socket Cable: 2 / 2.5 m (6.5 / 8.2 ft)	AC Adapter / Cigar Socket Cable: 2 / 2.5 m (6.5 / 8.2 ft)			
Dimensions (L x W x H)	867 x 465 x 476 mm (34-1/8 x 18-1/4 x 18-3/4")	663 x 341 x 372 mm (26-1/8 x 13-3/8 x 14-5/8")	456 x 245 x 308 mm (18 x 9-5/8 x 12-1/8")			
Net weight	25.6 - 29.0 kg (56.4 - 63.9 lbs.)	13.8 - 17.3 kg (30.4 - 38.1 lbs.)	7.9 - 9.4 kg (17.4 - 20.7 lbs.)			
Standard Equipment : Shoulder Belt (CW001G / CW003G), AC Adaptor (Country-specific), Cigar Socket Cable						

Not covered by EPTA-Procedure

Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202208



Cordless Cooler & Warmer Box CW002G / CW001G / CW003G







-18°c~60°c [0°f~140°f]







-18°c ~60°c [0°F~140°F]



-10°C [15_{°F}]

5°C

Freeze the ice pack

Cool the drink

Warm the caulk tube

Caulk tubes to be warmed must be brand new and unopened. Also caulk tubes must be stored in the box within the storage temperature range recommended by the manufacturer of caulk tubes.*

*Do not store opened caulk tubes with foods because they produce volatile gas.

Compatible with 4 power sources





CW002G

The large capacity of 50L, which can be used by multiple persons, enables to keep a lot of items cold or hot.

(13.2gal)



About 15 x 2L PET bottles can be stored vertically.

Work amount on full battery charge

-18°C [0°F] 8 h

5°C [40°F] 19.5 h

60°C [140°F **4.5** h



both sides Compact yet highly rigid due to retractable



Inner tray



Enables to make the most of the inside top space of the box of injury even if you the cap to drain to store small items. release your hand.

Top cover with damper function



Softly closes to minimize the chance storage box, open

Drain cock



When cleaning the water from the box.

Drag handle that can be locked at 90°



transportation on casters.

The same features and benefits as those of CW001G/CW003G



U-shaped carry handle

By attaching optional Shoulder belt, you can also

hang this box on your

shoulder.





Able to store up to four 2L plastic bottles

Work amount on full battery charge

with two BL4040 batteries

22.5 h

60°C [140°F] **7** h



2/3 XGT battery port

USB output Bottle opener lamps water resistance port







CW001G

(5.3gal)









Compact design

Convenient size for one to several people.

(1.8gal)



Able to store six 500mL plastic bottles vertically (up to 220mm in height).

5°C [40°F]

60°C [140°F] **5.5** h









13.5 h

1 LXT battery port 2 XGT battery port