

# Angle Grinder GA7080, GA7081, GA7082 180 mm (7") GA9080, GA9081, GA9082 230 mm (9")



# 2,700 W motor with Anti-restart function, **Anti-vibration main handle and Soft start**

# **Indication lamp**

The indication lamp lights up green when the tool is plugged.

### **Anti-restart function**

The tool does not start with the switch being lock-oneven when the tool is plugged. At this time, the indication lamp blinks in red to show the unintentional restart proof device is



**Torque limiter** 

Minimizes the chance of overtightening the lock nutat startups and in heavy duty applications.

Large trigger switch

### **Rotatable main handle**

Can be positioned to suit most cutting and grinding operations.



Side handle: Anti-vibration side handle (country-specific)

Low vibration main handle and side handle

# Accessories

# **Dust collecting wheel guard**

for diamond cutting wheel

GA7080: Part No. 198514-2 Max cutting depth: 35mm

GA9080: Part No. 198440-5 Max cutting depth: 60mm



Wheel cover

GA7080, GA7081, GA7082 180 mm (7")

GA9080, GA9081, GA9082 230 mm (9")

for cut-off wheel

GA7080:

Part No. 122914-4

GA9080: Part No. 122913-6



**Dust collect cover** 

for 180mm offset diamond wheel

Part No. 191X44-6



Loop handle set

Part No. 199176-9



**Dust cover attachment set** 

can be attached to the air vent to reduce ingress of dust.

Part No. 191T14-1





# **Angle Grinder**

# GA7080, GA7081, GA7082 180 mm (7")

# GA9080, GA9081, GA9082 230 mm (9")



Double Insulation



Soft Start



Continuous Rating Input Wheel Diameter No Load Speed (RPM) Sound Pressure Level Sound Power Level

Dimensions (L x W x H) Net weight

Power supply cord

65 Trường Chính, P. I ĐT: 0243 202 2585

6.3-6.8 kg 2.5 m

GA7080 2,700W 180 mm (7") 8,500 94 dB(A) 102 dB(A) surface grinding with anti vibration side grip 5.9 m/s<sup>2</sup> 509 x 200 x 144 mm

GA7081 2,700W 180 mm (7") 8,500 94 dB(A 102 dB(A) surface grinding with anti vibration side grip 5.9 m/s 461 x 200 x 144 mm 6.1-6.6 ka

GA7082 180 mm (7") 8,500 94 dB(A) 102 dB(A) surface grinding with anti vibration side grip 5.9 m/s<sup>2</sup> 461 x 200 x 144 mm 6.0-6.5 ka

GA9080 2,700W 230 mm (9") 6,600 95 dB(A) 103 dB(A) surface grinding with 509 x 250 x 144 mm

anti vibration side grip 5.3 m/s 6.5-8.6 kg

GA9081 230 mm (9") 6,600 95 dB(A) 103 dB(A) surface grinding with anti vibration side grip 5.3 m/s<sup>2</sup> 461 x 250 x 144 mm 6.3-8.4kg

GA9082 2,700W 230 mm (9") 6,600 95 dB(A) 103 dB(A) surface grinding with anti vibration side grip 5.3 m/s² 461 x 250 x 144 mm 6.2-8.3 ka

Standard Equipment: GA7080/GA7081/GA7082; Grip 37 (143486-6), lock nut wrench 35 (782034-2), wheel cover 180k(122889-7) GA9080/GA9081/GA9082: Grip 37 (143486-6), lock nut wrench 35 (782034-2), wheel cover 230k (122891-0)

The weight may differ depending on the attachment(s). The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equi,

CONG TY TNHH MAKITA VIẾT NAM (DIL 456, Block 15, 1812-2 Bloog số 3, MCN VSP N. P. Hoà Phụ, TP, Thủ Đâu Một, Binh Dương, Di 7, 0274-362 8338 - Fair, 0274-362 8338 - Videotite: www.arakifa.com.um

CHÍ NHÁNH CTY TNHH MAKÍTA VN TAÍ MIỀN BẮC TRUNG TÂM DỊCH VỤ KHÁCH HÀNG Fax: 0222 376 5941 TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH HÀ NÔI

Phương Liệt, Q. Thanh Xuân, TP. Hà Nội.

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH CẦN THƠ

CHÍ NHÁNH BUÔN MA THUỘT TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH HẢI PHÒNG

CHI NHÁNH NHA TRANG Ló 36.38 dường BB, Khu đó thị Vinh Điệm Trung, Xã Vinh Ngọc TP. Nha Trang, T, Khánh Hòa ĐT: 0258 220 0039 TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHÍ NHÁNH HỒ CHÍ MINH Số 12 Trịnh Văn Cần, P. Cầu Ông Lãnh, Q. 1, TP. Hồ Chi Minh ĐT: 0283 821 5191

A4-052023-2