



Makita® Cordless Jig Saw JV002G / JV001G

XGT 40V LITHION max

■ Cordless Jig Saw series

	Top Handle	Barrel handle
40V max	JV002G 	JV001G
18V	DJV182 DJV184 	DJV181 DJV185
12V max	JV103D 	

■ Accessories ● Standard Equipment JV002GZ

Dust nozzle assembly For dust collection Part No. 122C71-6 ●	Anti-splintering device Part No. 192557-6	Guide rule set Part No. 193516-3	Guide rail adapter set Part No. 193517-1 197252-3	Rule bar set Part No. 195842-6	Guide rail Overall length: 1m 199140-0 1.4m 194368-5 1.5m 199141-8 1.9m 194925-9
---	---	--	--	--	--

■ Charging Time

	Fast Charging DC40RA	DC40RC
*1 BL4020 2.0Ah	22 min	30 min
*1 BL4025 2.5Ah	28 min	38 min
*1 BL4040/F 4.0Ah	45 min	67 min

*1 Recommended battery

Cordless Jig Saw	JV002GZ / JV001GZ
	Variable Speed
	Brake
	Anti-restart function
	Constant Speed
	Soft Start
	Orbital Cutting
	Bayonet Shank
	Dust Collection
	Toolless blade change
	Built-in Job Light
	Carrying Case
	JV002GZ: Battery & charger are sold separately JV001GZ: Battery & charger are sold separately Standard Equipment: JV002GZ: Dust nozzle assembly (122C71-6), cover plate (413J99-0), anti-splintering device (415524-7), hex. wrench 4 (783202-0), jigsaw blade set 2 pcs (jigsaw blade No.B22 (for steel/Inox/ plastic/aluminium) / B10 (for wood/plastic) / BR13 (for wood)). JV001GZ: Cover plate (413J99-0), anti-splintering device (415524-7), hex. wrench 4 (783202-0), jigsaw blade set 2 pcs (jigsaw blade No.B22 (for steel/Inox/ plastic/aluminium) / B10 (for wood/plastic) / BR13 (for wood)).

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

AL-122033-2



Top Handle
JV002G



Barrel handle
JV001G



Cutting speed 20% up

Compared to predecessor 18V model



CÔNG TY TNHH MAKITA VIỆT NAM

Kho 5/5, Số 1, Đường Số 6, KCN - BT - DV VSP Bắc Ninh, P. Phú Châu, TP. Từ Sơn, T. Bắc Ninh,ĐT: 0222 376 5942 Fax: 0222 376 5941

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH ĐÀ NẴNG
 Số 40, Đường Chi Lăng, P. Hải Châu II, Q. Hải Châu, TP. Đà Nẵng,ĐT: 0236 352 5079 / 0236 352 5179 Fax: 0236 352 5478

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH HẢI PHÒNG
 Số 01 (ĐH01), Dũ An Hoàng Huy Riverside, P. Thượng Lý, Q. Hồng Bàng, TP. Hải Phòng,ĐT: 0225 389 4358 Fax: 0225 389 4358

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH HỒ CHÍ MINH
 Số 12, Trinch Văn Cảnh, P. Cầu Ông Lãnh, Q. 1, TP. Hồ Chí Minh,ĐT: 0283 821 5191

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH HÀ NỘI
 65 Trường Chinh, P. Phương Liệt, Q. Thanh Xuân, TP. Hà Nội,ĐT: 0243 202 2585

High power

BL MOTOR



Constant speed control

XGT technology and constant speed control reduce the chance of drop in cutting speed, providing excellent cutting performance higher than our current and competing models in a wide range of applications from thin metal cutting to 48mm thick MDF cutting.

Top Handle JV002G



Lock-off button

Variable speed control by trigger
allows for easier precise alignment of the blade with pencil line.



Barrel handle JV001G



Electronic push button switch
located on both sides of Housing



3 Orbital settings + Straight cutting



Optimum cutting action can be selected by simply turning the change lever.

Position	Cutting action	Applications
0	Straight line cutting	Cuts in mild steel, stainless steel and plastics Clean cuts in wood and plywood
I	Small orbital cutting	Cuts in mild steel, aluminum and hard wood
II	Medium orbital cutting	Cuts in wood and plywood Fast cuts in aluminum and mild steel
III	Large orbital cutting	Fast cuts in wood and plywood

Variable speed control by dial



photo:
JV002G

Number	Workpiece
4 - 6	Wood
3 - 6	Mild steel
3 - 4	Stainless steel
3 - 6	Aluminum
1 - 4	Plastics

Toolless blade clamp



with a blade holder which allows for one-hand blade change

LED job light




(Twin LEDs with light up function during standby mode)

Light reduction function

- Less glare when cutting metal
- Press and hold the main power button for 3 brightness settings.
- Memory function: The tool remembers the job light brightness set last time and the light will light up at that brightness when turned on.

Dust Collection



Front cuff 24 (option)

Dust nozzle can be set to Base firmly with Thumb screw.

Dust nozzle can be attached over the sawdust exhaust port for connection to Makita vacuum cleaner.

SOFT NOLOAD New Soft no-load

- Easy, precise alignment of blade with pencil line at cut starting point
- With disabling function
- If the tool detects no-load motor rotation during intermittent operation such as precision cut-out, it switches automatically back to Soft no-load mode.

Bevel range

0 to 45° left and right.



Less wobbling

Improved stability during cutting due to a wider base plate

XPT
Extreme Protection Technology