



Cordless Fan CF003G 40Vmax / 18V / AC



XGT
40V Li-ION
max

18V
LITHIUM-ION

450 mm fan diameter



- Compatible with
- 40Vmax XGT Li-Ion battery
 - 18V LXT Li-Ion battery
 - AC (through AC adapter)



AC





Front fan cover has been redesigned to supply air widely around the appliance therefore, this model is suited for air blowing or ventilation in a large place such as factory, warehouse, etc.

Max air flow volume
120 m³/min

Max air speed*
300 m/min
*Measured at 1.0 m away from the appliance

Compatible with 40Vmax / 18V Li-Ion battery / AC

Stepless air flow volume setting

Can be mounted onto MAKPAC cart



XGT battery and LXT battery can be installed simultaneously.



Dial-style air flow volume adjustment (38 - 120m³/min)



Portability can be enhanced by mounting the appliance onto MAKPAC cart.

Manual angle adjustment of fan head

Automatic oscillation

Accessory case



90° up/45° down with a locking knob



Automatic oscillation angle adjustment: 60°, 90°, 120° left/right



Located on the front of the appliance for storing AC adapter, etc.



Foldable carrying handle

Continuous use (approx)

on a full battery charge [at Max air speed]

Battery	Without oscillation	With oscillation
BL1860B	90 min	85 min
BL4040	115 min	110 min
BL4080F	230 min	220 min



Three Off timer settings
1 hour, 2 hours, 4 hours

Charging Time

	Fast Charging		Standard Charging			Fast Charging		Standard Charging	
	DC40RA	DC40RC	DC18RC	DC18SD					
BL4020 2.0Ah	22 min	30 min	BL1815N 1.5Ah	15 min	30 min				
BL4025 2.5Ah	28 min	38 min	BL1820B 2.0Ah	24 min	45 min				
BL4040 4.0Ah	45 min	67 min	BL1830B 3.0Ah	22 min	60 min				
BL4050F 5.0Ah	50 min	85 min	BL1840B 4.0Ah	36 min	90 min				
BL4080F 8.0Ah	76 min	170 min	BL1850B 5.0Ah	45 min	110 min				
			BL1860B 6.0Ah	55 min	130 min				

Cordless Fan

CF003GZ 40Vmax / 18V / AC

Variable Speed	Air velocity	96-300 m/min
	Air flow	38-120 m ³ /min
	Fan diameter	450 mm (17-3/4")
	Fan head angle adjustment	Up: 90° / Down: 45° Left: 90° / Right: 90°
	Automatic oscillation	Left: 60, 90, 120° Right: 60, 90, 120°
	Continuous use (min.) w/o oscillation	w/ BL4040: 115 / w/ BL4080F: 230 / w/ BL1860B: 90
	Continuous use (min.) w/ oscillation	w/ BL4040: 110 / w/ BL4080F: 220 / w/ BL1860B: 85
	Dimensions (L x W x H)	w/o Battery: 312 x 633 x 770 mm (12-1/4 x 25 x 30-1/4") w/o Battery: 7.9 kg (17.4 lbs.)
	Net weight	
	CF003GZ : Battery & charger are sold separately	
	Standard Equipment : AC adaptor (TE00000793), power supply cord (TE00000779)	

not covered by EPTA-Procedure

Items of standard equipment and specifications may vary by country or area.

A4-082023-1

CÔNG TY TNHH MAKITA VIỆT NAM

CHI NHÁNH CTY TNHH MAKITA VN TẠI MIỀN BẮC
Khu 5, Số 1, Đường Số 6, KCN - DT - DV VSP, Bắc Ninh, P. Phú Chấn,
TP. Từ Sơn, T. Bắc Ninh.
ĐT: 0222 376 5942 Fax: 0222 376 5941

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG
CHI NHÁNH HÀ NỘI
65 Trường Chinh, P. Phương Liệt, Q. Thanh Xuân, TP. Hà Nội,
ĐT: 0243 202 2385

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG
CHI NHÁNH ĐÀ NẴNG
Số 40, Đường Chi Lăng, P. Hải Châu 1, Q. Hải Châu, TP. Đà Nẵng
ĐT: 0236 352 5078 / 0236 352 5178 Fax: 0236 352 5479

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG
CHI NHÁNH CẦN THƠ
386 Võ Văn Kiệt, Khu Vực 5, P. An Thới, Q. Bình Thủy,
TP. Cần Thơ.
ĐT: 0292 389 4358 Fax: 0292 389 4359

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG
CHI NHÁNH BUỒN MA THUỘT
Số 1 Lê Đức Thọ, P. Thống Nhất, TP. Buôn Ma Thuột, T. Đắk Lắk,
ĐT: 0262 355 4556 Fax: 0262 355 4557

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG
CHI NHÁNH HẢI PHÒNG
Số 01 Lô D101, Dự án Hoàng Huy Riverside, P. Thượng Lý,
Q. Hồng Bàng, TP. Hải Phòng.
ĐT: 0225 883 1529

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG
CHI NHÁNH NHA TRANG
Là 3636 đường B6, Khu đô thị Vinh Diêm Trung, Xã Vinh Ngọc,
TP. Nha Trang, T. Khánh Hòa
ĐT: 0258 220 0039

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG
CHI NHÁNH HỒ CHÍ MINH
Số 12 Trịnh Văn Căn, P. Cầu Ông Lãnh, Q. 1, TP. Hồ Chí Minh,
ĐT: 0283 821 5191