





Easy operation

Developed specially for cutting only, allowing for lightweight design to provide excellent maneuverability.

DTC100

Max blade opening width: 50 mm (2")



DTC101

Max blade opening width: 50 mm (2")



DTC102

Max blade opening width: 65 mm (2-9/16")



DTC103

Max blade opening width: 54 mm (2-1/8")





DTC101

Max blade opening width: 50 mm (2")

- Open type for easy cutting of cable at desired position.
- For cutting Al / Cu cable.







DTC103

Max blade opening width: 54 mm (2-1/8")

- · Closed type.
- For cutting ACSR (Aluminum Conductors Steel Reinforced).



ACSR (Aluminum Conductors Steel Reinforced)

ACSR cable consists of galvanized steel strands used as core reinforcement and solid aluminum strand conductors vound around the core.

This cable is, therefore, widely used for long-distance power transmission due to its high strength and low weight.

Automatic reverse function

• Auto-reverse function when a cut has been completed.

photo: DTC101

• After cutting, the motor stops and the blade automatically returns to the set position when the forward switch is released.

Forward switch OFF





Accessories Shoulder belt Part No. 161347-8

Blade return volume can be adjusted to suit the diameter of the cable to be cut.

LED job light

One LED with afterglow function





Charging Time

Cutting completed

18V	DC18RC	DC18SD
BL1815N 1.5Ah	15 min	30 min
BL1820B 2.0Ah	24 min	45 min
BL1830B 3.0Ah	22 min	60 min
BL1840B 4.0Ah	36 min	90 min
BL1850B 5.0Ah	45 min	110 min
BL1860B 6.0Ah	55 min	130 min

Cordless Cable Cutter

photo: DTC101

Blade stops at set position

Cutting

completed

DTC100ZK / DTC101ZK / DTC102ZK / DTC103ZK

		DTC100 / DTC101	DTC102	DTC103
■ Built-in Job Light	Max blade opening width	50 mm	65 mm	54 mm
	Max cable cutting capacity	600V-CV: 500mm ² single-core (φ38mm)	Non-ferrous materials only	ACSR: Al 550mm ² /ST 70mm
Standard Equipment : DTC100ZK:		6600V-CV: 500mm ² single-core (φ45mm)	(Al or Cu): 65 mm	
		600V-IV: 500mm ² single-core (φ35mm)		
DTC101ZK: Stationary blade (ZM00000191), moving blade (ZM00000175) DTC102ZK:		600V-VVR: 150mm ² triple-core (φ47mm)		
	Dimensions (L x W x H)	DTC100:	w/BL1830B/BL1840B/	w/BL1830B/BL1840B/
		w/BL1830B/BL1840B/BL1850B/BL1860B:	BL1850B / BL1860B:	BL1850B / BL1860B:
		116 x 197 x 363 mm (4-9/16 x 7-3/4 x 14-1/4")	116 x 240 x 401 mm	116 x 240 x 401 mm
		DTC101:	(4-9/16 x 9-1/2 x 15-3/4")	(4-9/16 x 9-1/2 x 15-3/4")
		w/BL1830B/BL1840B/BL1850B/BL1860B:		
		116 x 190 x 430 mm (4-9/16 x 7-1/2 x 17")		
moving blade (ZM00000194)	Net weight	DTC100: 2.9 kg (BL1860B)	3.5 kg (BL1860B)	5.5 kg (BL1860B)
		DTC101: 3.6 kg (BL1860B)		
TC103ZK:				
ationary blade (ZM00000210),	DTC100ZK/DTC101ZK/DTC103ZK: Battery & charger are sold separately			
noving blade (ZM00000209)				

ding to EPTA-Procedure 01/2014, are shown in the table. Items of standa

CÔNG TY TNHH MAKITA VIÊT NAM NIN 456, Block 16, 181,12 Busing 66 3, KON NSP A, P, Head Print, P2 This Date Majt, Blend Dusting, Brit O2074 552 8338 - Fast: 0274 582 8338 - Website: www.makita.com/un

CHI NHÁNH CTY TNHH MAKITA VN TAI MIỀN BẮC TRUNG TÂM DỊCH VỤ KHÁCH HÀNG Kho 5, Số 1, Đường Số 6, KCN - ĐT - DV VSIP Bắc Ninh, P. Phù Chắn TP. Từ Sơn, T. Bắc Ninh. ĐT: 0222 376 5942 Fax: 0222 376 5941 TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH HÀ NỘI 65 Trường Chinh, P. Phương Liệt, Q. Thanh Xuân, TP. Hà Nội. 9T: 0243 202 2585

CHI NHÁNH ĐÀ NẪNG

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH CẦN THƠ

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH BUÔN MA THUỘT 68 Lẽ Đức Thọ, P. Tháng lợi, IP. Buôn Ma Thuột, T. Đák Lắk. DT: 0262 355 4556 Fax: 0262 355 4557

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH HẢI PHÒNG

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH NHA TRANG Ló 36-38 đượng Bộ, Khu đó thị Vinh Điềm Trung, Xã Vinh Ngọc TP. Nha Trang, T. Khánh Hòa ĐT: 0258 220 0039 TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHÍ NHÁNH HỒ CHÍ MINH Số 12 Trịnh Văn Cần, P. Cầu Ông Lãnh, Q. 1, TP. Hồ Chi Minh. ĐT: 0283 821 5191