

Satisfy Professional's Needs



**Cordless Breaker
HM004G**



28.6mm Hex
Shank Type

40V^{Li-ion}max + **40V^{Li-ion}max**



**High power
similar to
corded models**

Impact energy

72.8 Joule

Low Vibration

6.5 m/s²



XGT X2
80Vmax



40Vmax + 40Vmax

Powered by two 40Vmax XGT
Li-Ion batteries in series
(80Vmax)

BL
MOTOR

High power
brushless
motor

Impact energy
72.8 Joule



Low Vibration thanks to **AVT**
(Anti-Vibration Technology)


Vibration level **6.5 m/s²**

Active dynamic vibration absorber moves in the opposite direction to the drive piston to reduce vibration.

Vibration absorbing housing

provides a practical combination of high power and low vibration.

Vibration absorbing spring (4 places)



Slim body for excellent visibility

219mm



Hex shank: 28.6mm

Self sharpening bull point
(Country-specific)

AWS (Auto-start Wireless System)

Connects to compatible vacuum cleaner with Bluetooth. The vacuum cleaner automatically runs while the switch is on.

Bluetooth

Vacuum cleaner is activated



Switch on the tool

Wireless unit
Main power switch



Counter weight mechanism

reduces vibration during chipping operation.



Counterweight


Piston

SOFT NO LOAD

Suppression of motor speed during no-load



During no-load



Under load

XPT

(eXtreme Protection Technology)

Accessories

Dust extractor attachment set

w/o hose
Part No. 197168-2

w/ hose
Part No. 197148-8



**With Sensomatic chip

Charging Time

	Fast Charging		Standard Charging	
	DC40RA	DC40RB	DC40RC	DC40WA
BL4020 2.0Ah	22 min	30 min	30 min	110 min
BL4025 2.5Ah	28 min	38 min	38 min	130 min
* BL4040/F 4.0Ah	45 min	67 min	67 min	210 min
* BL4050F 5.0Ah	50 min	85 min	85 min	260 min
* BL4080F 8.0Ah	76 min	170 min	170 min	420 min

*1 Recommended battery

Main power switch

Battery capacity warning lamp



Maintenance warning lamp

LED job light

Twin LEDs with preglow and afterglow functions



Cordless Breaker

HM004GZ05 1-1/8" : 28.6mm Hex Shank

- 28.6mm Hex Shank
- Constant Speed
- Soft Start
- Built-in Job Light
- Anti-restart function

Impact energy	72.8 J
Blows per minute (BPM)	870
Shank diameter	28.6 mm
Sound power level	103 dB(A)
Sound pressure level	95 dB(A)
Vibration level	6.5 m/s ²
Dimensions (L x W x H)	882 x 227 x 540 mm
Net weight	29.6 kg (BL4025F x2)
	32.1 kg (BL4080F x2)

HM004GZ05: Battery & charger are sold separately

Standard Equipment : Hex wrench 5 (783203-8), 28.6mm hex self sharpening



The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area. RA-042024-1

CÔNG TY TNHH MAKITA VIỆT NAM

Kho 4.56, Block 16, 16/1/12 Đường số 3, KCN VSFP, P. Hòa Phú, TP. Thủ Đức, Bình Dương
ĐT: 0274 362 8338 - Fax: 0274 362 8338 - Website: www.makita.com.vn

CHI NHÁNH CTY TNHH MAKITA VN TẠI MIỀN BẮC

CHI NHÁNH ĐÀ NẴNG
Số 40, Bờm Chi Lăng, P. Hải Châu II, Q. Hải Châu, TP. Đà Nẵng
ĐT: 0236 352 9379 / 0236 352 9379 Fax: 0236 352 9479

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH HÀ NỘI

65 Trường Chinh, P. Phương Liệt, Q. Thanh Xuân, TP. Hà Nội,
ĐT: 0243 202 2585

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH CẦN THƠ

368 Võ Văn Kiệt, Khu Vực 5, P. An Thới, Q. Bình Thủy,
TP. Cần Thơ,
ĐT: 0292 389 4358 Fax: 0292 389 4359

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH BUƠN MA THUỘT

Số 14 Bờm Chi Lăng, TP. Thuận An, TP. Thuận An, TP. Bắc Ninh,
ĐT: 0282 355 4558 Fax: 0282 355 4557

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH HẢI PHÒNG

Số 01 Lê Đình, Dự án Hoàng Huy Riverside, P. Thăng Lý,
Q. Hồng Bàng, TP. Hải Phòng,
ĐT: 0225 883 1529

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH NHA TRANG

Lô 36-38 đường B6, Khu đô thị Vinh Diễm Trung, Xã Vinh Ngọc,
TP. Nha Trang, T. Khánh Hòa
ĐT: 0259 220 0039

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH HỒ CHÍ MINH

Số 12 Trịnh Văn Căn, P. Cầu Ông Lãnh, Q. 1, TP. Hồ Chí Minh,
ĐT: 0283 821 5191