



Cordless Pole Saw DUA200

Easy pruning of high branches



With three-stage pipe

Reaches branches up to	Lightweight
about 3,500 mm*	3.5 kg**

With two-stage pipe

Reaches branches up to	Lightweight
about 2,500 mm*	2.9 kg**



- BL1815N: 1.5Ah
- BL1820B: 2.0Ah
- BL1830B: 3.0Ah
- BL1840B: 4.0Ah
- BL1850B: 5.0Ah
- BL1860B: 6.0Ah

Accessories ● Standard Equipment

Guide bar 8 set				Saw chain 8 set						Guide bar case 210	Sprocket 7 set	
Bar length	Motor Mount	Type	Part No.	No. of drive links	gauge	pitch	Type OREGON	Cutter type	Part No.	Part No.	Type	Part No.
20 cm/8"	A041	Sprocket nose bar	191453-3 ●	38	1.1 mm / .043"	.325"LP	80TXL	MC	191451-7 ●	413G28-5 ●	Sprocket .325"LP	1911W5-9 (pack) 227947-5 (no pack) ●

Band assembly
Part No. 122D94-0 ●

Chain edger set
Part No. D-70948
File size: 4 mm

Charging Time

Battery	Fast Charging		Standard Charging	
	DC18RC	DC18SD	DC18RC	DC18SD
BL1815N 1.5Ah	15 min	30 min	15 min	30 min
BL1820B 2.0Ah	24 min	45 min	24 min	45 min
BL1830B 3.0Ah	22 min	60 min	22 min	60 min
BL1840B 4.0Ah	36 min	90 min	36 min	90 min
BL1850B 5.0Ah	45 min	110 min	45 min	110 min
BL1860B 6.0Ah	55 min	130 min	55 min	130 min

Cordless Pole Saw

DUA200Z01

- Brake
- Automatic Oiling
- Toolless blade change

Guide bar length	200 mm (8")
Chain speed	6.7 m/s
Saw chain	Type: 80TXL, Pitch: 0.325", Gauge: 1.1 mm (0.043")
Oil tank capacity	55 mL (1.9 oz.)
Sound pressure level	77 dB(A)
Sound power level	86 dB(A)
Vibration level	Cutting wood: 2.5 m/s ² or less
Dimensions (L x W x H)	w/o Guide bar: 1,620 / 2,520 x 85 x 134 mm (63-3/4 / 99 x 3-3/8 x 5-1/4")
Length from the rear end of Trigger to the Tool tip	w/o Guide bar: 1,460 - 2,360 mm (57-1/2 - 93")
Net weight	3.2 - 3.5 kg (7.1 - 7.7 lbs.)
Net weight (Battery)	BL1815N - BL1860B
Net weight (Attachment)	Guide bar, Saw chain, Chain oil

DUA200Z01: Battery & charger are sold separately.

Standard Equipment: Sprocket 7 (227947-5), band assembly (122D94-0), guide bar 8 set (191453-3), guide bar case 210 (413G28-5), saw chain 8 set (191451-7).

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area. A3-082024-1

CÔNG TY TNHH MAKITA VIỆT NAM

- CHI NHÁNH CTY TNHH MAKITA VN TẠI MIỀN BẮC**
Khu 5, Số 1, Đường Số 6, KCN - BT - DV VSP Bắc Ninh, P. Phú Châu, TP. Từ Sơn, T. Bắc Ninh, BT: 0222 376 5942 Fax: 0222 376 5941
- TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH ĐÀ NẴNG**
Số 40, Đường Chi Lăng, P. Hải Châu 1, Q. Hải Châu, TP. Đà Nẵng, BT: 0236 352 5079 / 0236 352 5179 Fax: 0236 352 5478
- TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH HỒ CHÍ MINH**
65 Trường Chinh, P. Phường Lữ, Q. Thanh Xuân, TP. Hồ Chí Minh, BT: 0243 202 2585
- TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH BUỒN MA THUỘT**
88 Lê Đức Thọ, P. Thới Mỹ, TP. Thuận An, TP. Bình Dương, BT: 0262 355 4556 Fax: 0262 355 4557
- TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH HẢI PHÒNG**
Số 01 Lê Đình, Đ. An Hoàng, P. Hoàng Mai, TP. Hải Phòng, BT: 0225 883 1579
- TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH NHÀ TRANG**
Lô 36-38 đường B6, Khu đô thị Vĩnh Diễm Trung, Xã Vĩnh Ngọc, TP. Nhà Trng, T. Khánh Hòa, BT: 0262 220 0039
- TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH HỒ CHÍ MINH**
Số 12 Trinch Văn Cấn, P. Cầu Ông Lãnh, Q. 1, TP. Hồ Chí Minh, BT: 0283 821 5191



*Height to the underside of Saw chain **w/ Battery: BL1860B, Guide bar and Saw chain

With the lightweight head section, the tool ensures high work efficiency and easy pruning of high branches.



Head angle adjustment

- The angle of the tool head is adjustable in 9 stages between 60° upwards and 60° downwards.
- The angle adjustment can be locked/unlocked with one touch.





BL
MOTOR

High Power Brushless Motor



Automatic chain lubrication




Tool-less chain adjustment



Automatic chain tension adjustment by simply loosening and retightening the lever

Slim tool head



The slim shape of the tool head allows for easy insertion between branches.

Branch hook



Hook for pulling and dropping branches that have been caught

Lock-off buttons on both left and right sides



Battery guard

With three-stage pipe

Reaches branches up to
about **3,500 mm***
about
Tool length: 2,500 mm

Lightweight
3.5 kg**

* Height to the underside of Saw chain
**w/ Battery BL1860B, Guide bar and Saw chain

With two-stage pipe

Reaches branches up to
about **2,500 mm***
about
Tool length: 1,300 mm

Lightweight
2.9 kg**

* Height to the underside of Saw chain
**w/ Battery BL1860B, Guide bar and Saw chain

XPT

eXtreme Protection Technology

Cutting work amount

Work volume on a single full battery charge

About **600** cuts

- 50 mm cedar square timber
- saw chain : 80TXL
- Battery : BL1860B

