

■ **Accessories Standard Equipment:** HR2670X5 ● HR2670FT ●

Dust cup set

A dust collection attachment to be attached to the tip of the tool and used in conjunction with a vacuum cleaner.

For drilling work

HR2670: Part No. 1914L7-6
HR2670FT: Part No. 1914L8-4



For chiseling work

HR2670: Part No. 1914L9-2
HR2670FT: Part No. 1914M0-7



Dust extraction pad set

Part No. 1914X3-8

Sticking the pad to the wall with the suction power of Vacuum cleaner enables drilling into concrete while collecting dust.



Tool holder set

HR2670FT: Part No. 191F47-2



Drill chuck set

HR2670FT: Part No. 191F46-4 ●



Chuck adapter (SDS-PLUS)

Part No. D-14093



Drill chuck set

Part No. 194041-7 ●



Grease vessel set

Part No. 194683-7
Hammer bit grease



Combination Hammer

HR2670/HR2670X5/HR2670FT 26 mm (1") 3.0 J Combination Hammer, SDS-PLUS

- Double Insulation
- Variable Speed
- Reversing
- Torque Limiter
- Built-in Job Light (HR2670FT only)
- Adapted for SDS-PLUS bits
- Carrying Case

	HR2670	HR2670FT
Impacts per minute	0-4,500 min ⁻¹	0-4,500 min ⁻¹
No load speed	0-1,500 min ⁻¹	0-1,500 min ⁻¹
Continuous rating input	800 W	800 W
Capacity	Concrete (w/ TCT bit): 26 mm Concrete (w/ Core bit): 68 mm Concrete (w/ Diamond core bit): 80 mm Steel: 13 mm Wood: 32 mm	Concrete (w/ TCT bit): 26 mm Concrete (w/ Core bit): 68 mm Concrete (w/ Diamond core bit): 80 mm Steel: 13 mm Wood: 32 mm
Impact energy	3.0 J	3.0 J
Vibration level (EN62841-2-6)	Hammer drilling into concrete: 16.1 m/s ² Chiselling: 14.2 m/s ²	Hammer drilling into concrete: 15.7 m/s ² Chiselling: 14.0 m/s ²
Sound pressure level (EN62841-2-6)	94 dB(A)	94 dB(A)
Sound power level (EN62841-2-6)	102 dB(A)	102 dB(A)
Dimensions (L x W x H)	362 x 77 x 207 mm	390 x 77 x 207 mm
Net weight	2.78 kg (tool only)	2.71 kg (tool only)

Standard Equipment: HR2670: Grip assembly (122G56-6), depth gauge (321144-6).
HR2670X5: Grip assembly (122G56-6), depth gauge (321144-6), bull point 250 (D-08713), drill chuck set (194041-7), sds-plus bit set (5pcs/set) (D-17784).
HR2670FT: Grip assembly (122G56-6), drill chuck set (191F46-4), depth gauge (321144-6).



Combination Hammer
HR2670 / HR2670FT

26 mm (1") Adapted for SDS-PLUS bits



Powerful 800 W motor delivers 3.0 J of impact energy to handle the most demanding applications

photo: HR2670

HR2670
Normal chuck



HR2670FT
Quick change chuck with LED job light



The weight may differ depending on the attachment(s), including the battery cartridge. Items of standard equipment and specifications may vary by country or area.

A3-102024-2

CÔNG TY TNHH MAKITA VIỆT NAM

Kho 456, Block 16, 19L1-2 Đường số 3, KCN VSPP, P. Hòa Phú, TP. Thủ Đức, Bình Dương
ĐT: 0274 362 8338 - Fax: 0274 362 8339 - Website: www.makita.com.vn

CHI NHÁNH CTY TNHH MAKITA VN TẠI MIỀN BẮC
Khu 5, Số 1, Đường Số 6, KCN - BT - DV VSP Bắc Ninh, P. Phú Châu, TP. Từ Sơn, T. Bắc Ninh
ĐT: 0222 376 5942 Fax: 0222 376 5941

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH HÀ NỘI
85 Trường Chinh, P. Phương Liệt, Q. Thanh Xuân, TP. Hà Nội
ĐT: 0243 202 2585

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH ĐÀ NẴNG
Số 40, Đường Chi Lăng, P. Hải Châu 1, Q. Hải Châu, TP. Đà Nẵng
ĐT: 0236 352 5079 / 0236 352 5179 Fax: 0236 352 5478

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH CẦN THƠ
366 Vĩ Văn Kiệt, Khu Vực 5, P. An Thủy, Q. Bình Thủy, TP. Cần Thơ
ĐT: 0292 389 4358 Fax: 0292 389 4359

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH BUƠN MA THUỘT
88 Lê Đức Thọ, P. Thắng Mĩ, TP. Buôn Ma Thuột, T. Đắk Lắk
ĐT: 0262 355 4556 Fax: 0262 355 4557

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH HẢI PHÒNG
Số 01 Lê Đức Thọ, Di An Hoàng Hới Riverside, P. Thượng Lý, Q. Hồng Bàng, TP. Hải Phòng
ĐT: 0225 863 1529

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH NHA TRANG
Số 56-58 đường B6, Khu đô thị Vinh Diễm Trung, Xã Vinh Ngọc, TP. Nha Trang, T. Khánh Hòa
ĐT: 0258 220 0639

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH HỒ CHÍ MINH
Số 12 Trịnh Văn Cấn, P. Cầu Ông Lãnh, Q. 1, TP. Hồ Chí Minh
ĐT: 0283 821 5191

Superior Power and Durability

By redesigning the internal structure and optimizing the motor specifications, we have achieved increased power and durability, ensuring superior performance.

Impact energy
3.0 J

Drilling efficiency

Drilled holes downward into concrete with compressive strength of 40N/mm² to a depth of 60mm (2-3/8") at a pressing load of 8kg using a two-flute bit

HR2670 ø16.0mm	125
HR2670 ø10.5mm	105
predecessor model	100



Hammer drilling using the rotation with hammering mode
photo: HR2670



Chiselling with the hammering mode
photo: HR2670

Dust cup (Optional accessory)

- Compact and highly visible dust cup
- The bellows for drilling and for chiseling can be exchanged with one touch.

Bellows for drilling



Bellows for chiseling



Attachment



HR2670

HR2670FT

One-touch sliding chuck

Quick change drill chuck

(HR2670FT only)



Adapted for SDS-PLUS bits



Compact



Reverse switch using Brush holder unit

The same speed and torque even in the reverse rotation



Variable speed control by trigger

Lock-on button

Three operation modes

Rotation only / Rotation with hammering / Hammering only



LED job light

(HR2670FT only)



photo: HR2670

Drilling with the rotation mode

photo: HR2670FT with Quick change chuck