



Cordless Impact Driver DTD156



Max fastening torque **155N·m**



Work amount
on a single full
battery charge

560 pcs.

Drove 90mm coarse thread
screws into melapi.
with BL1850B (5.0Ah)



Max fastening torque: 155N·m

Aluminum hammer case

Driving shank:
6.35 (1/4) Hex

LED Job light
with pre-glow and afterglow
functions



Compact and lightweight
4-pole motor

Variable speed control by
trigger

Ergonomically designed
handle, Rubberized soft
grip

Belt clip (hook)

	Part No.
Short	346449-3
Long	346317-0



BL1815N 1.5Ah	15 min	30 min
BL1820B 2.0Ah	24 min	45 min
BL1830B 3.0Ah	22 min	60 min
BL1840B 4.0Ah	36 min	90 min
BL1850B 5.0Ah	45 min	110 min
BL1860B 6.0Ah	55 min	130 min

Cordless Impact Driver

DTD156SF1J / DTD156FE / DTD156Z 5

- Variable Speed
- Brake
- Reversing
- Built-in Job Light
- Carrying Case

DTD156SF1J: 1 battery 3.0Ah (BL1830B), charger (DC18SD)
Connector plastic case type 2(821550-0)
DTD156FE: 2 battery 3.0Ah (BL1830B), charger (DC18SD)
DTD156Z: Battery & charger are sold separately
Standard equipment:
(+) Truss head screw M4X12 (266622-8), hook (346317-0)
DTD156SF1J: Twist Torsion bit PH2-120 (E-10833).

Capacity	Machine Screw: M4 - M8 (5/32" - 5/16") Standard Bolt: M5 - M14 (3/16" - 9/16") High Strength Bolt: M5 - M12 (3/16" - 1/2") Coarse thread (in length): 22 - 125 mm (7/8" - 4-7/8")
Hex Shank	6.35 mm (1/4")
No Load Speed (RPM)	0 - 2,500
Impacts Per Minute (IPM)	0 - 3,000
Max Fastening Torque	155 N·m (1,370 in.lbs.)
Vibration Level	10.0 m/s ²
Sound Pressure Level	92 dB(A)
Sound Power Level	103 dB(A)
Dimensions (L x W x H)	w/ BL1815N / BL1820B: 143 x 79 x 223 mm (5-5/8 x 3-1/8 x 8-3/4") w/ BL1830B / BL1840B / BL1850B / BL1860B: 143 x 79 x 241 mm (5-5/8 x 3-1/8 x 9-1/2")
Net weight	1.3 - 1.6 kg (2.9 - 3.6 lbs.)

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.

Items of standard equipment and specifications may vary by country or area.

A4-052023-1

CÔNG TY TNHH MAKITA VIỆT NAM

Kho 4-5-6, Block 16, 18L12 Đường số 3, KCN VSP, P. Hòa Phú, TP. Thủ Đức, Bình Dương
ĐT: 0274 362 8338 - Fax: 0274 362 8339 - Website: www.makita.com.vn

CHI NHÁNH CTY TNHH MAKITA VN TẠI MIỀN BẮC
Khu S, Số 1, Đường Số 6, KCN - BT - DV VSP Bắc Ninh, P. Phú Chấn,
TP. Từ Sơn, T. Bắc Ninh,
ĐT: 0222 376 5942 Fax: 0222 376 5941

**TRUNG TÂM DỊCH VỤ KHÁCH HÀNG
CHI NHÁNH HÀ NỘI**
65 Trường Chinh, P. Phương Liệt, Q. Thanh Xuân, TP. Hà Nội,
ĐT: 0243 202 2385

**TRUNG TÂM DỊCH VỤ KHÁCH HÀNG
CHI NHÁNH ĐÀ NẴNG**
102 Trần Nữ Hoàng, P. Hải Châu 2, Q. Hải Châu, TP. Đà Nẵng,
ĐT: 0236 352 5078 / 0236 352 5179 Fax: 0236 352 5479

**TRUNG TÂM DỊCH VỤ KHÁCH HÀNG
CHI NHÁNH CẦN THƠ**
386 Võ Văn Kiệt, Khu Vực S, P. An Thới, Q. Bình Thủy,
TP. Cần Thơ,
ĐT: 0292 389 4358 Fax: 0292 389 4359

**TRUNG TÂM DỊCH VỤ KHÁCH HÀNG
CHI NHÁNH BUỒN MA THUỐC**
88 Lê Đức Thọ, P. Thống Nhất, TP. Buon Ma Thuột, T. Đắk Lắk,
ĐT: 0262 355 4556 Fax: 0262 355 4557

**TRUNG TÂM DỊCH VỤ KHÁCH HÀNG
CHI NHÁNH HẢI PHÒNG**
Số 01 Lô D1H1, Dự án Hoàng Huy Riverside, P. Thượng Lý,
Q. Hồng Bàng, TP. Hải Phòng,
ĐT: 0225 883 1529

**TRUNG TÂM DỊCH VỤ KHÁCH HÀNG
CHI NHÁNH NHA TRANG**
Là 3636 đường B6, Khu đô thị Vinh Diêm Trung, Xã Vinh Ngọc,
TP. Nha Trang, T. Khánh Hòa
ĐT: 0258 220 0039

**TRUNG TÂM DỊCH VỤ KHÁCH HÀNG
CHI NHÁNH HỒ CHÍ MINH**
Số 12 Trịnh Văn Căn, P. Cầu Ông Lãnh, Q. 1, TP. Hồ Chí Minh,
ĐT: 0283 821 5191