Satisfy Professional's Needs

XG



Trakita Cordless Impact Driver



Excellent fastening performance in heavy-duty tasks

Max fastening torque 230 N·m

ALLER CONTRACTORS AND ADDRESS AND ADDRES



heavy-duty tasks, such as tightening hex head or hexalobular (star-shaped) hole head course thread screws, which are less prone to cam-out.



Thakita





Max fastening torque

230 N·m

- Delivers excellent fastening performance in heavy-duty tasks, such as tightening hex head or hexalobular (star-shaped) hole head course thread screws, which are less prone to cam-out.
- Capable of smoothly fastening screws on hard materials, such as LVL (Laminated Veneer Lumber)

4-stage impact power selection + **T-mode** (for thin metal sheets only)

- The impact power can be adjusted to four stages to match the type of screw and material.
- For tasks requiring attention to cam-out, such as with Phillips head screws, the impact force can be adjusted accordingly.
- Equipped with the T-Mode to minimize screw stripping, which is likely to occur when a self-drilling screw is tightened into a thin metal sheet workpiece under light load.





T-mode

The brushless motor provides longer work hours per charge and extended tool life.

hak

Overall length

36 mm

makita

Reversing switch

Soft grip

Hook

One-touch bit installation Reduced resistance allows for easier bit installation.



LED job light Twin LEDs with preglow and afterglow functions



Variable speed control by trigger Allows for speed adjustments based on the material or application.

eXtreme Protection



Accessories **Tool hanger set**



Drill chuck Part No. 192173-4



Charging Time

40 V	Fast Charging) DC40RA	Standard Charging DC40RC	
*1 BL4020 2.0Ah	22 min	30 min	
*1 BL4025 2.5Ah	28 min	38 min	
*1 BL4040/F 4.0Ah	45 min	67 min	
BL4050F 5.0Ah	50 min	85 min	
BL4080F 8.0Ah	76 min	170 min	
*1 Recommended battery			

Cordless Impact Driver TD004GZ

Variable Speed	Capacity	Steel: 22 mm (7/8") / Wood (Auger bit): 24 mm (15/16")	
	Max fastening torque	230 N·m	
(maxe) Brake	No load speed	Max / Hard / Med. / Soft:	
\equiv		0 - 3,900 / 0 - 3,000 / 0 - 2,100 / 0 - 1,200 min ⁻¹	
C Reversing	Impacts per minute	Max / Hard / Med. / Soft:	
		0 - 3,900 / 0 - 3,600 / 0 - 3,100 / 0 - 1,900 min ⁻¹	
(Anti-restart function	Vibration level (EN62841-2-2)	Impact tightening of fasteners of the maximum	
		capacity of the tool: 23.5 m/s ²	
4 Electronic 4-Speed	Vibration K factor (EN62841-2-2)		
· ·		capacity of the tool: 1.5 m/s ²	
≣D Built-in Job Light	Sound pressure level (EN62841-2-2)	100 dB (A)	
	Sound power level (EN62841-2-2)	108 dB (A)	
Carrying Case	Noise K factor (EN62841-2-2)	3 dB (A)	
	Dimensions (L x W x H)	136 x 86 x 248 mm (BL4025)	
	Net weight	1.8 - 3.1 kg	
	(Battery)	BL4020-BL4080F	
TW011GZ: Battery & charger are sold separately.			
Step devide Equipment - Truce Lload Screw M4v12 (266622, 9), healt (246217, 0)			

Standard Equipment : Truss Head Screw M4x12 (266622-8), hook (346317-0)

MAKITA VIETNAM COMPANY LIMITED UNIT 456, Block 16, 181.12, Street No. 3, VSIP2, Binh Duong Ward Ho Chi Minh City

MAKITA VIETNAM COMPANY LIMITED NORTH BRANCH MAKITA VIETNAM COMPANY LIMITED - DA NANG MAKITA VIETNAM COMPANY LIMITED - BUON MA THUOT MAKITA VIETNAM COMPANY LIMITED - NHA TRANG Unit 5, No1, Road 6, Vsip Industrial Park, Tu Son Ward, Bac Ninh Province Tel: 0222 376 5942

MAKITA VIETNAM COMPANY LIMITED - HANOI BRANCH MAKITA VIETNAM COMPANY LIMITED - CAN THO Group 15 and No 4 Alley 63 Tuone Clinin Stress, Phuone Liet Ward, CITY, DRAMCU Hanoi City Tel: 0243 202 2585

CITY BRANCH 40 Chi Lang Hai C CITY BRANCH 366 Vo Van Kiet Street, Area 5, Binh Thuy Ward, Can Tho City Tel: 0292 389 4358

CITY BRANCH 68 Le Duc Tho, Buon Ma Thuot Ward, Dak Lak Province MAKITA VIETNAM COMPANY LIMITED - HAI PHONG CITY BRANCH No 01, Lot OH01, Hoang Huy Riverside, Thuong Ly Ward, Hong Bang Ward, Hai Phong City Tel: 0225 883 1529

CITY BRANCH Lot 3638, B6 Street, Vinh Diem Trung Urban Area, Tay Nha Trang Ward, Khanh Hoa Province Tech 0758 270 nona MAKITA VIETNAM COMPANY LIMITED - HO CHI MINH CITY BRANCH 12 Trinh Van Can, Ben Thanh Ward, Ho Chi Minh City Tel: 0283 821 5191