

Compact and Lightweight but provides High Torque Work

Light weight

at **2.5 kg**

Current Model

437 mm

PC5010C

350 mm

Variable speed control by Dial

also indicates as power supply lamp.

Ergonomically designed grip

Comfortable Loop handle

absorbs the vibration during operation

Removable front cover enables to plane flush to walls or corners.



Forced dust collection needs to connect with Vacuum cleaner to extract the dust.



Anti-restart function

- Prevents accidental start-up even if the tool is plugged to power source with the switch "ON".
- Blinking red LED at the rear cover warns that Anti-restart function has been activated.



Concrete Planer	PC5010C 125 mm (5")
Double Insulation	Continuous rating input 1,400W
Variable Speed	Wheel Diameter 125 mm (5")
Constant Speed	Hole Diameter 22.23 mm (7/8")
Soft Start	No Load Speed (RPM) 4,000 - 9,000
Dust Collection	Vibration Level Surface Grinding w/ Loop Handle: 5.5 m/s ²
Carrying Case	Sound Pressure Level 85.0 dB(A)
	Sound Power Level 96.0 dB(A)
	Dimensions (L x W x H) 350x231x179 mm (13-3/4"x9-1/8"x7")
	Net weight 2.5 - 3.6 kg (5.5 - 7.9 lbs.)
	Power supply cord 4.0 m (13.1 ft)
	Standard Equipment : Offset Diamond Wheel, Lock Nut Wrench

The weight may differ depending on the attachment(s), including the battery cartridge.
The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.
Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 201806



Concrete Planer PC5010C 125 mm (5")

**Superior handling in horizontal
and overhead applications**



Light weight
at **2.5 kg**

Powerful
1,400 W
(1,400W= continuous rating
power input)

Variable Speed
4,000 - 9,000 min⁻¹

