



**Cordless Edger
UE001G**



40V^{max} L^{Li-ION}

**High power output
similar to 30cm³ class
engine-powered edgers**



Max output

1.1 kW

Max cutting depth

59 mm

BL MOTOR AFT XPT

Powered by a 40Vmax XGT Li-Ion battery, equipped with a BL motor, and delivering a maximum output of 1.1 kW




Guard with high visibility of the blade

Guard with improved visibility of the blade tip while maintaining the coverage angle.



Cutting depth adjustment

The working depth can be adjusted by adjusting the tire height.



AFT

Active Feedback sensing Technology

shuts down current to the motor, if the rotation speed suddenly slows down (in the case of kick-back, etc.).

BL MOTOR



New lock-off mechanism

By adding a lock lever to the lock-off lever, we have revised the automatic power-off time, enhancing work efficiency.



XPT / IPX4
-compatible


High water-resistance allows the user to operate the tool even if it is wet with water.



Guard plate

Guard plate

Protects Gear case from wear due to contact with the ground during operation at the maximum cutting depth.



Accessories

● Standard Equipment

Blade set

Part No. 196745-7 ●



Charging Time

		Fast Charging	Standard Charging
		DC40RA	DC40RC
BL4020	2.0Ah	22 min	30 min
*1 BL4025	2.5Ah	28 min	38 min
*1 BL4040/F	4.0Ah	45 min	67 min
*1 BL4050F	5.0Ah	50 min	85 min
*1 BL4080F	8.0Ah	76 min	170 min

*1 Recommended battery

Cordless Edger

UE001G

	Variable Speed	Max output 1,100 W
	Brake	Blade diameter 203 mm (8")
	Constant Speed	Max cutting depth 59 mm (2-5/16")
	Soft Start	No load speed 0-4,800 min ⁻¹
	Anti-restart function	Continuous use w/BL4050F: 18 min (w/ load)
		Sound pressure level*1 75.5 dB (A)
		Sound power level*1 89.4 dB (A)
		Noise K factor*1 2.4 / 2.6 dB (A)
		Vibration level*2 2.5 m/s ² or less
		Vibration K factor*2 1.5 m/s ²
		Dimensions (L x W x H) w/ Blade, w/ out Battery 1,860 x 227 x 303 mm (73-1/4 x 8-15/16 x 11-7/8")
		Net weight 6.1 kg - 7.3 kg (13.4lbs - 16.1lbs)
		Net weight (Battery) BL4020 - BL4080F

Standard Equipment : **UE001GZ**. Battery & charger not include
Cap 24 (422A15-7), cap 24 (424434-7), blade (196745-7), box wrench 17 (782238-6), hex. wrench 4 (783202-0), accessory bag (831304-7).

The weight may differ depending on the attachment(s), including the battery cartridge.
Items of standard equipment and specifications may vary by country or area.

CÔNG TY TNHH MAKITA VIỆT NAM

Kho 4-5-6, Block 16, 18L12 Đường số 3, KCN VSP, P. Hòa Phú, TP. Thủ Đức, TP. Hồ Chí Minh
ĐT: 0274 362 8338 - Fax: 0274 362 8339 - Website: www.makita.com.vn

CHI NHÁNH CTY TNHH MAKITA VN TẠI MIỀN BẮC

Kho 5, Số 1 Đường Số 6, KCN - DT - DV VSP Bắc Ninh, P. Phú Châu, TP. Từ Sơn, T. Bắc Ninh.
ĐT: 0222 376 5942 Fax: 0222 376 5941

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH HÀ NỘI

65 Trường Chinh, P. Phương Liệt, Q. Thanh Xuân, TP. Hà Nội.
ĐT: 0243 202 2385

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH ĐÀ NẴNG

Số 40, Đường Chi Lăng, P. Hải Châu, Q. Hải Châu, TP. Đà Nẵng
ĐT: 0236 352 5070 / 0236 352 5170 Fax: 0236 352 5470

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH CẦN THƠ

386 Võ Văn Kiệt, Khu Vực 5, P. An Thới, Q. Bình Thủy, TP. Cần Thơ.
ĐT: 0292 389 4358 Fax: 0292 389 4359

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH BUỒN MA THUỘT

Số Lê Đức Thọ, P. Thống Kê, TP. Buon Ma Thuột, T. Đắk Lắk.
ĐT: 0262 355 4556 Fax: 0262 355 4557

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH HẢI PHÒNG

Số 01 Lô D1-01, Dự án Hoàng Huy Riverside, P. Thượng Lý, Q. Hồng Bàng, TP. Hải Phòng.
ĐT: 0225 883 1529

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH NHA TRANG

Là 3636 đường B6, Khu đô thị Vinh Diễm Trung, Xã Vinh Ngọc, TP. Nha Trang, T. Khánh Hòa
ĐT: 0258 220 0039

TRUNG TÂM DỊCH VỤ KHÁCH HÀNG

CHI NHÁNH HỒ CHÍ MINH

Số 12 Trịnh Văn Căn, P. Cầu Ông Lãnh, Q. 1, TP. Hồ Chí Minh.
ĐT: 0283 821 5191