



**Cordless Impact Driver
DTD201**

Satisfy Professional's Needs



High-speed, high-power for heavy-duty tasks



Max fastening torque

210 N·m

High-speed rotation

Max

3,700 min⁻¹



Enhanced hammer and spring with increased motor speed deliver superior fastening performance to our previous model.

Work efficiency*

DTD201

160

Our 18V model 100

*Drove coach screws (lag screws) with a length of 90mm and a diameter of 9.0mm into melapi.

One-touch bit installation

Reduced resistance allows for easier bit installation.



Anti-bit wobbling structure

Ensures enhanced stability during fastening.

LED job light

Twin LEDs with preglow and afterglow functions



Variable speed control by trigger

Allows for speed adjustments based on the material or application.

Soft grip

Ergonomic rubberized soft grip for increased comfort

Reversing switch

Hook



4-stage impact power selection + T-mode (for thin metal sheets only)

Four selectable speed settings make it easy to adjust the tool for a wide range of applications.



4-stages

- 4 (Max)
- 3 (Hard)
- 2 (Medium)
- 1 (Soft)

T-mode

XPT

eXtreme Protection Technology



Charging Time

	DC18RC	DC18SD
18V LITHIUM-ION		
*1BL1815N 1.5Ah	15 min	30 min
*1BL1820B 2.0Ah	24 min	45 min
*1BL1830B 3.0Ah	22 min	60 min
*1BL1840B 4.0Ah	36 min	90 min
*1BL1850B 5.0Ah	45 min	110 min
*1BL1860B 6.0Ah	55 min	130 min
BL1890 9.0Ah	85 min	200min
BL18120 12.0Ah	120min	265min
18V LITHIUM-ION	LXT BASIC	DCB18WA
Compatible with charger DCB18WA only		
BLB182 2.0Ah		90 min

*1 Recommended battery

Accessories

Tool hanger set

Part No. 191K57-9



Hook set

Part No. 194654-4



Battery protector set

Part No. 194649-7



Cordless Impact Driver

DTD201Z/DTD201RTJ

- Variable Speed
- Brake
- Reversing
- Electronic 4-Speed
- Built-in Job Light
- Carrying Case

Capacity	Steel: 22 mm/ Wood (Auger bit): 24 mm
Max fastening torque	210 N·m
No load speed	Max / Hard / Med. / Soft: 0 - 3,700 / 0 - 3,200 / 0 - 2,100 / 0 - 1,100 min ⁻¹
Impacts per minute	Max / Hard / Med. / Soft: 0 - 4,400 / 0 - 4,200 / 0 - 3,600 / 0 - 2,000 min ⁻¹
Vibration level	9.9 m/s ² (EN62841-2-2, Mode: impact tightening with max. capacity)
Sound pressure level	97 dB (A) (EN62841-2-2)
Sound power level	105 dB (A) (EN62841-2-2)
Dimensions (L x W x H)	121 x 81 x 246 mm (BL1860B)
Net weight	1.3kg (BL1815N) ~ 2.3kg (BL18120)
DTD201Z: Battery & charger are sold separately.	
DTD201RTJ: 2 batteries 5.0 Ah BL1850B (197280-8), fast charger (DC18RC).	

Standard Equipment : Truss head screw M4X12 (266622-8), hook (346317-0).

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area. [A4-102025-1]

MAKITA VIETNAM COMPANY LIMITED

UNIT 4-5-6, Block 16, 18L12, Street No 3, VSP II, Binh Duong Ward, Ho Chi Minh City
Tel: 0274 362 8338 - Fax: 0274 362 8339 - Website: www.makita.com.vn

MAKITA VIETNAM COMPANY LIMITED NORTH BRANCH
Unit 5, No.1, Road 6, Vsp Industrial Park, Tu Son Ward,
Bac Ninh Province
Tel: 0222 376 5942

MAKITA VIETNAM COMPANY LIMITED - HANOI BRANCH
Group 15 and No.4 Alley 63 Truong Chinh Street, Phuong Liet Ward,
Hanoi City
Tel: 0243 202 2585

MAKITA VIETNAM COMPANY LIMITED - DA NANG
CITY BRANCH
40 Chi Lang, Hai Chau Ward, Da Nang City
Tel: 0236 3525 179

MAKITA VIETNAM COMPANY LIMITED - CAN THO
CITY BRANCH
366 Vo Van Kiet Street, Area 5, Binh Thuy Ward, Can Tho City
Tel: 0292 389 4358

MAKITA VIETNAM COMPANY LIMITED - BUON MA THUOT
CITY BRANCH
68 Le Duc Tho, Buon Ma Thuot Ward, Dak Lak Province
Tel: 0262 355 4556

MAKITA VIETNAM COMPANY LIMITED - HAI PHONG
CITY BRANCH
No 01, Lot 04/01, Hoang Huy Riverside, Hong Bang Ward, Hai Phong City
Tel: 0225 883 1529

MAKITA VIETNAM COMPANY LIMITED - NHA TRANG
CITY BRANCH
Lot 36-38, 86 Street, Vinh Diem Trung Urban Area, Tay Nha Trang Ward, Khanh Hoa Province
Tel: 0258 220 0039

MAKITA VIETNAM COMPANY LIMITED - HO CHI MINH
CITY BRANCH
12 Trinh Van Can, Ben Thanh Ward, Ho Chi Minh City
Tel: 0283 821 5191