



Magnetic Drill

HB351 / HB501 / HB850

35 mm (1-3/8") / 50 mm (2") / 85 mm (3-3/8")

Powerful magnetic drilling for steel and other ferrous metals

Powerful magnetic clamping force

HB351: **11,000 N**

HB501: **12,000 N**

HB850: **22,000 N**

Magnet type: Electromagnet



HB351



HB501



HB850

Model	HB351	HB501	HB850
Max. cutting diameter	ø35 mm (1-3/8")	ø50 mm (2")	ø85 mm (3-3/8")
Max. cutting depth	50 mm (2")	50 mm (2")	75 mm (2-15/16")
No load speed (mechanical speed change)	Single speed: 790 min ⁻¹	2-speed: 450 / 750 min ⁻¹	3-speed: 170 / 320 / 470 min ⁻¹

Delivers secure magnetic holding power for stable, precise drilling.



Photo: HB501

Oil tank

Installing the oil tank higher than the cutting tool allows oil to flow to the blade tip by gravity.



Integrated carrying handle

for easy carrying of tool

Feed handle attachable to either side

The feed handle can be attached to either side, depending on the work environment.

Magnetic base

Produces powerful clamping force for increased accuracy and stability while drilling.
Fixing method: Electromagnet

Accessories

T.C.T cutter

Cutting depth: 35mm

Diameter	Part No.	Diameter	Part No.
12	B-90641	26	B-90716
14	B-90657	28	B-90722
16	B-90663	32	B-90738
18	B-90679	36	B-90744
20	B-90685	40	B-90750
22	B-90691	50	B-90766
24	B-90700		



Cutting depth: 50 mm

Diameter	Part No.	Diameter	Part No.
12	B-90772	26	B-90847
14	B-90788	28	B-90853
16	B-90794	32	B-90869
18	B-90803	36	B-90875
20	B-90819	40	B-90881
22	B-90825	50	B-90897
24	B-90831	64	B-90906

Center pin

Model	Size	Part No.
HB351	6x104mm	ES00000075
HB501	8x105mm	ES00000076
	8x155mmL	ES00000223
HB850	6x118mm	ES00000224
	7x118mm	ES00000225

Safety belt

HB850: Part No. ES00000074

Chuck adapter 1/2-20UNF

HB351: Part No. ES00000079

Drill drift MT3

HB850: Part No. ES00000222

MT3 sleeve

SA-19 mm weldon

HB850: Part No. ES00000226

Magnetic Drill

HB351 / HB501 / HB850 35 mm (1-3/8") / 50 mm (2") / 85 mm (3-3/8")

- Mechanical 2-Speed
HB501 only
- Mechanical 3-Speed
HB850 only
- Carrying Case
HB351, HB501 only

	HB351	HB501	HB850
Continuous rating input	1,050 W	1,200W	1,800 W
Cutting capacity diameter	35 mm (1-3/8")	50 mm (2")	85 mm (3-3/8")
Cutting capacity depth	50 mm (2")	50 mm (2")	75 mm (2-15/16")
No load speed	790 min ⁻¹	450 / 750 min ⁻¹	170 / 320 / 470 min ⁻¹
Magnetic clamping force	11,000 N	12,000 N	22,000 N
Dimensions (L x W x H)	263 x 156 x 323 mm	270 x 156 x 432 mm	364 x 272 x 622 mm
Net weight	10.5 kg	17.5 kg	29 kg

Standard Equipment: **HB351:** Center pin 6X104mm (ES00000075), center pin 8X105mm (ES00000076), center pin case (ES00000077), hex socket head set screw M10X (ES00000066), safety belt (ES00000074), fuse ceramic 2A 250VAC 5x20mm (ES00000035), hex. wrench 2.5 (783208-8), hex. wrench 3 (783201-2), hex. wrench 4 (783202-0), combination wrench 8mm (ES00000078), chuck adapter 1/2-20UNF (ES00000079)
HB501: Center pin 6X104mm (ES00000075), center pin 8X105mm (ES00000076), center pin case (ES00000077), hex socket head set screw M10X (ES00000121), safety belt (ES00000074), fuse ceramic 2A 250VAC 5x20mm (ES00000035), hex. wrench 2.5 (783208-8), hex. wrench 3 (783201-2), hex. wrench 4 (783202-0), hex. wrench 5 (783217-7), combination wrench 8mm (ES00000078)
HB850: Center pin 8X155MM (ES00000223), center pin 6X118MM (ES00000224), center pin 7X118MM (ES00000225), center pin case (ES00000077), hex socket head set screw M10X (ES00000121), safety belt (ES00000074), fuse ceramic 2A 250VAC 5x20mm (ES00000035), hex. wrench 2.5 (783208-8), hex. wrench 3 (783201-2), hex. wrench 4 (783202-0), hex. wrench 5 (783217-7), hex. wrench 6 (783204-6), combination wrench 8mm (ES00000078), drill drift MT3 (ES00000222), MT3 sleeve SA-19MM weldon (ES00000226)

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area. [AA-042026-1](#)

MAKITA VIETNAM COMPANY LIMITED

UNIT 4-5-6, Block 16, 18L12, Street No 3, VSP II, Binh Duong Ward, Ho Chi Minh City
Tel: 0274 362 8338 - Fax: 0274 362 8339 - Website: www.makita.com.vn

MAKITA VIETNAM COMPANY LIMITED NORTH BRANCH
Unit 5, No1, Road 6, Vsp Industrial Park, Tu Son Ward,
Bac Ninh Province
Tel: 0222 376 5942

MAKITA VIETNAM COMPANY LIMITED - HANOI BRANCH
Group 15 and No4 Alley 63 Trung Chinh Street, Phuong Liet Ward,
Hanoi City
Tel: 0243 202 2585

MAKITA VIETNAM COMPANY LIMITED - DA NANG
CITY BRANCH
40 Chi Lang, Hai Chau Ward, Da Nang City
Tel: 0236 3525 179

MAKITA VIETNAM COMPANY LIMITED - CAN THO
CITY BRANCH
95 Song Hanh Street, Tay Do Cultural Residential Area,
Cai Rang Ward, Can Tho City
Tel: 0292 389 4358

MAKITA VIETNAM COMPANY LIMITED - BUON MA THUOT
CITY BRANCH
88 Le Duc Tho, Buon Ma Thuot Ward, Dak Lak Province
Tel: 0262 355 4556

MAKITA VIETNAM COMPANY LIMITED - HAI PHONG
CITY BRANCH
No 13, Lot TDC 13, Tho Lu Street, Hong Bang Ward, Hai Phong City
Tel: 0225 883 1529

MAKITA VIETNAM COMPANY LIMITED - NHA TRANG
CITY BRANCH
Lot 36-38, 86 Street, Vinh Diem Trung Urban Area, Tay Nha Trang Ward, Khanh Hoa Province
Tel: 0258 220 0039

MAKITA VIETNAM COMPANY LIMITED - HO CHI MINH
CITY BRANCH
12 Trinh Van Can, Ben Thanh Ward, Ho Chi Minh City
Tel: 0263 821 5191